

Listing of Claims:

1. (Original) A load-sensing element comprising:

a block of substantially rectangular cross section
which is braced on a first end and which is adapted to receive a
load to be measured on a second end; and

5 a single strain gauge disposed on the block;

wherein the block is pierced by an opening which is
shaped such that at least two joints are created on each of a top
side of the block and an underside of the block;

wherein the two joints on one of the top side and lower
10 side of the block are offset from one another so as to compensate
for a force eccentricity which occurs upon non-central
introduction of the load to be measured; and

wherein the single strain gauge is disposed on the
block in a vicinity of one of the offset joints.

2. (Original) The load-sensing element of claim 1, wherein
a shoulder is formed on the top side of the block so as to offset
the two joints on the top side of the block.

3. (Original) The load-sensing element of claim 2, wherein
the two joints on the top side of the block each have a same
material thickness.

4. (Original) The load-sensing element of claim 1, wherein the opening in the block comprises two different shaped portions.

5. (Original) The load-sensing element of claim 4, wherein the two different shaped portions of the opening have different heights.

6. (Original) The load-sensing element of claim 4, wherein the one of the two different shaped portions is substantially circular, and the other of the two different shaped portions is substantially oval.

7. (Original) The load-sensing element of claim 6, wherein the offset joints are respectively positioned above or below the substantially circular portion of the hole and the substantially oval portion of the hole.

8. (Original) The load-sensing element of claim 7, wherein the single strain gauge is disposed on the block in a vicinity of the one of the offset joints that is positioned above or below the substantially oval portion of the opening.

9. (Original) The load-sensing element of claim 1, wherein the offset is provided in a middle portion between the two joints on the top side of the block.

10. (Currently Amended) An electronic scale comprising:
four load-sensing elements each respectively arranged on one of four branches of a Wheatstone Bridge circuit arrangement;

5 wherein each of the four load-sensing elements comprises a block of substantially rectangular cross section which is pierced by an opening that is shaped to form offset adjacent pivot points for compensating for a force eccentricity which occurs upon non-central introduction of a load to be
10 measured;

 wherein only one strain gauge is disposed in each of the four branches of the Wheatstone Bridge circuit arrangement in association with one of the four load-sensing elements for measuring deformation at one of the offset adjacent pivot points
15 of each of the four load-sensing elements; and

 wherein respective ~~diametrically opposed pairs~~ opposite
ones of the four strain gauges are disposed to be deformed in opposite directions.

11. (Currently Amended) The electronic scale of claim 10,
wherein the four strain gauges comprise a first diametrically
opposed pair of strain gauges and a second diametrically opposed
pair of strain gauges, and wherein ~~the first diametrically~~
5 ~~opposed~~ each pair of strain gauges ~~is arranged~~ includes one
strain gauge with an upward orientation and ~~the second~~
~~diametrically opposed pair of strain gauges is arranged~~ one
strain gauge with a downward orientation.

12. (Original) The electronic scale of claim 10, wherein
signal changes in the load-sensing elements disposed in adjacent
branches of the Wheatstone Bridge circuit arrangement are added
together.